

RS1000-P4.81 Outdoor Rental LED Display




Module & cabinet:



Features:

- Suitable for P2.604, P2.976, P3.91, P4.81 outdoor
- Arc structure is optional
- cost-effective cabinet
- Location pins left and right for fast assembly
- Lightweight only 13kg per panel
- Super thin, only 88mm thickness
- Power connectors & ethernet connectors are easy to assemble & disassemble



Application:

Stage Performance
 Conference
 Celebration
 banquet
 exhibition

Technical Specifications(RS1000-P2.604 outdoor):

Pixel Pitch	P4.81
LED type	SMD1921
Pixel configuration	3-in-1 SMD
Pixel density	43,264 pixels/m ²
Module dimension(W*H)	250mmx250mm
Module resolution	52*52dots
Drive Method	1/13 scan
Maintenance	back
Cabinet size (W*H)	500*1000mm
Cabinet depth	88mm
Cabinet material	Aluminum
Cabinet weight	13kg/pcs
Brightness	≥4000 cd/m ²
Best Viewing Distance	5m to 50m
Viewing Angle	140 * 140
Grey Level	14 Bit
Refresh Rate	≥1920HZ /3840HZ
Power consumption(Avg.)	120w/cabinet
Power consumption(Max.)	390w/cabinet
Humidity-operating	10% ~ 95%
Operating Temperature	-20° - 50° C
Screen life	≥100000 hours
Controlling System	Synch or Async
Certificates	CE,RoHs,FCC,UL
Ingress Protection (IP)	IP65
Warranty	3 Years

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.