

## RL1000-P2.976 Outdoor Rental LED Display



### Module & cabinet:



Back




Front



Side

### Features:

- Suitable for P2.604, P2.976, P3.91, P4.81 outdoor
- Arc structure is optional
- Easy-to-change LED modules on the power supply and snap-on doors
- Location pins left and right for fast assembly
- Lightweight only 13kg per panel
- Super thin, only 88mm thickness
- Power connectors & ethernet connectors are easy to assemble & disassemble



## Application:

Stage Performance     
  Conference     
  Celebration     
  banquet     
  exhibition

## Technical Specifications(RL1000-P2.97 outdoor):

Pixel Pitch	P2.97
LED type	SMD1415
Pixel configuration	3-in-1 SMD
Pixel density	112,896 pixels/m <sup>2</sup>
Module dimension(W*H)	250*250mm
Module resolution	84*84dots
Drive Method	1/21 scan
Maintenance	back
Cabinet size (W*H)	500*1000mm
Cabinet depth	88mm
Cabinet material	Aluminum
Cabinet weight	13kg/pcs
Brightness	≥4500 cd/m <sup>2</sup>
Best Viewing Distance	3m to 30m
Viewing Angle	140 * 140
Grey Level	14 Bit
Refresh Rate	≥1920HZ /3840HZ
Power consumption(Avg.)	140w/cabinet
Power consumption(Max.)	400w/cabinet
Humidity-operating	10% ~ 95%
Operating Temperature	-20° - 50° C
Screen life	≥100000 hours
Controlling System	Synch or Async
Certificates	CE,RoHs,FCC,UL
Ingress Protection (IP)	IP65
Warranty	3 Years

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to SZLEDWORLD.